

**beLine70AHV 175 W**

only available with PowerBox

2018

light source **80 x OSRAM**

total consumption **175 W ± 5 %**

LED output @ **+ 25 °C    + 50 °C    + 80 °C**

total lm (LED) **28.204 lm    27.075 lm    25.383 lm**

lm / wat (LED) **161 lm/wat    155 lm/wat    145 lm/wat**

T<sub>J</sub> (°C) **65 °C    85 °C    100 °C**

luminaire output @ 25 °C **24.909 lm - 27.075 lm**

LED working @ **41% [820 mA]**

input voltage **PowerBox 200 [192VDC]**

LED driver **Inventronics LED driver in PowerBox**

LED driver efficiency **93,0%**

power factor @ full power **99%**

colour temperature **4000 K**

CRI **> 70**

secondary optics **no optics, N, W, WW, WWW**

radio dimming **standard in PowerBox**

PIR sensor **not available**

operating temperature **-30 °C to +80 °C**

mounting height **8 m to 40 m**

lamp lifespan **L70@70.000 hrs@80°C**

warranty on all components **50.000 hrs or 5 years**

housing – heatsink **extruded 99,7% aluminum**

optics cover **3.2 mm extra white tempered glass**

connection **IP66 connector**

cooling surface **1,22 m<sup>2</sup>**

IP rating **IP65**

IK code **IK08**

protection class IEC **class I**

rough service mark **YES**

lamp dimensions **A/B/C = 625/315/130 mm**

lamp weight **11,5 kg**

packaging dimensions **A/B/C = 725/320/150 mm**

packaging weight **11,0 kg**



**Photometric curves**




N NARROW(30°)



W WIDE(49°)



WW VERYWIDE(64°)



WWW VERYVERYWIDE(104°)

## beLine70AHV 175 W

only available with PowerBox

Lamp version	optics	lm output	efficiency
175W beLine 70AHV [FR] - 80OGWN470-00FREE00-600A1	<b>NO OPTICS</b>	27.075 lm	155 lm/wat
175W beLine 70AHV [N] - 80OGWN470-00C13233-600A1	<b>N (NARROW)</b>	25.180 lm	144 lm/wat
175W beLine 70AHV [W] - 80OGWN470-00C14605-600A1	<b>W (WIDE)</b>	25.451 lm	145 lm/wat
175W beLine 70AHV [WW] - 80OGWN470-00C14606-600A1	<b>WW (VERYWIDE)</b>	24.909 lm	142 lm/wat
175W beLine 70AHV [WWW] - 80OGWN470-00C14724-600A1	<b>WWW (VERYVERYWIDE)</b>	25.451 lm	145 lm/wat

### PowerBox connection

All beLine70AHV lamps are only available with the PowerBox unit.


*All beLine70AHV lamps have no LED driver inside the lamp due to HIGH temperatures they can be used on.*

*All beLine70AHV lamps can not be plugged to a standard 100VAC or 230VAC system but on PowerBox DC system.*

*The cable from PowerBox unit to beLine 70AHV lamp has to be 2x1,5mm<sup>2</sup> to prevent major voltage loses on cables.*

beLine 70AHV lams can be installed up to 100 m from the POERBOX unit under DC current.

For technical details and installation note please refere to PowerBox datasheet.



### Mounting kit options



Reflector MC



Wall MC



Low ceiling MC




Steel chain



Wire hanging kit

### Heat sink design

Unique linear design with vertical ribs allows the LEDs to have an optimal heat dissipation without a worry of them overheating. Side vertical ribs allow the dust to fall off the lamp and prevent accumulation of dust on the vital parts of the lamp.



### Certificates and protection