

beLINEAR PL 75 W

June 2018

light source **OSRAM LEDs**

total consumption **75 W ± 5 %**

LED output @ + 25 °C + 40 °C

total lm (LED) **14.351 lm 13.777 lm**

lm / wat (LED) **191 lm/wat 184 lm/wat**

T_J (°C) **55 °C 70 °C**

luminaire output @ 25 °C **10.194 lm (136 lm/W)**

LED working @ **36% [55 mA]**

input voltage **190-230 V**

input frequency **50 - 60 Hz**

LED driver **Tridonic LC, LCI series**

LED driver efficiency **90,0%**

power factor @ full power **95%**

colour temperature **4000 K**

CRI > 80

secondary optics **MILKY DIFUSOR PROTECTION**

operating temperature **-30 °C to +40 °C**

mounting height **2 m to 7 m**

lamp lifespan **L70@70.000 hrs**

warranty on all components **5 years**

housing – heatsink **extruded 99,7% aluminum**

optics cover **PMMA cover**

connection **IP66 connector**

cooling surface **0,37 m²**

IP rating **IP65**

protection class IEC **class I**



rough service mark **YES**

lamp dimensions **A/B/C = 1200/112/69 mm**


lamp weight **4,3 kg**

packaging dimensions **A/B/C = 1300/117/89 mm**


packaging weight **4,8 kg**



FAST MOUNTING



Photometric curves



MILKY PROTECTION
10.194lm (136lm/wat)